

Used to Scald Birds in a temperature-controlled tank for easy de-feathering



Features


- SS 304 constructed tank with stand
- Integrated with Hy-cab / Manual / Semi Automatic plants
- Analog temperature indicator
- Gas fitting arrangements

SCALDING TANK

Integrates with Automatic Poultry Processing Conveyor Plant

6 +.2)0\$2(1 4+2* 5 \$% .+2
 6 +.2)0\$2(1 4+2* (-+ 32/-)\$2+& ,\$.2
 6 +.2)0\$2(1 4+2* (-+ 32/-)\$2+& ,\$.2

Scalding Tank- Front View



Specifications

Scalding tanks are available in 3 types of capacities depending on the plant capacity or your requirement:

- 18" Diameter
- 24" Diameter
- 30" Diameter

Technical Data	18"	24"	30"
Single Phase 115/220VAC(+/-15%), 50Hz			
Three Phase 415VAC (+/-15%),50Hz			
HP			
KW			
Height	894	954	954
Length			
Width	457	610	762

CORPORATE OFFICE
 RND AUTOMATION PVT LTD • 1/4 Shiv Complex • Kondhwa Budruk • Pune 411 048 • Maharashtra • India
 Tel: +91 20 26930100 • 26930936 • Fax: +91 20 26930226
 Email: sales@rndautomation.co.in

WEBSITE
www.rndautomation.co.in

